



Maximum Lifting Capacity 65.0 Tons (58.97 Metric Tons)

Overall Length 18' 0" (5.49 m) Fully Closed
23' 0" (7.01 m) Counterweight Fully Extended

Overall Width 7' 0" (2.13 m)

Overall Height 9' 9" (2.97 m)

Lift Height 9' 9" to 24' 8" (2.97 m to 7.52 m)

Weight without Counterweight 19.0 Tons (17.24 Metric Tons)

Weight with Counterweight 35.0 Tons (31.75 Metric Tons)
16.0 Tons (14.52 Metric Tons) of Modular removable counterweight

Prime Power Dual fuel- Gasoline/Propane

Transmission Hydrostatic

Controls Electric over hydraulic

Steering Rear wheel, Power steering pivot to 61 degrees

Cylinders Hydraulic, 4 stage, Double acting

RIGGERS™

65 Ton Tri Lifter Load Chart (16 Tons Counterweight)

		C o u n t e r w e i g h t E x t e n s i o n				
		0 in	24 in	36 in	48 in	60 in
B o o m E x t e n s i o n	24 in	65 tons	65 tons	65 tons	65 tons	65 tons
	36 in	54	62	65	65	65
	48 in	43	50	53	56	60
	60 in	36	42	45	47	50
	72 in	31	36	38	41	43
	84 in	27	32	34	36	38
	96 in	24	28	30	32	34
			With Optional 10 and 12 foot boom extension			
108 in	22 tons	25 tons	27 tons	29 tons	31 tons	
120 in	20	23	24	26	28	
132 in	18	21	22	24	26	
144 in	16	19	20	22	24	

Note: Do not exceed 50 tons in top lift stage.

Based Upon 1.5:1 Safety Factor With Regard to Tipping

RIGGERS™